



NO	ACCESSORIES	CODE
1	Seat & Cover - Urea Soft Close	USCNMTCU168SWT
2	Floor Fixing Bolts	UYU1065K
3	Outlet Connector - TD 305 mm / TD 260 mm	UCON01 / UCON10
4	Internal Fitting 5/3L	SNLC3317DFBB5_3SQGBT1
5	S/Steel Flexible Hose - 18"	UOFP45T
6	Angle Valve	UOAV305
UNLESS NOTED OTHERWISE ALL DIMENSION IN mm. TOLERANCE : ≥ 75 mm : ± 2 % < 75 mm : ± 5 %		
		DRAFTING STANDARD BS 308
		DRAWN HASLAM
		CHECKED JOHAN
		APPROVED
REV	DESCRIPTION	DATE
1		27 - Jan - 16

SILVERDALE

INFORMATION CONTAINED IN THIS TECHNICAL DOCUMENT IS CONFIDENTIAL & REMAINS THE PROPERTY OF CLAY INDUSTRIES SDN BHD - VITREOUS CHINA DIVISION.

DRAWING TITLE : **WC 4467 B c/w LC 3317**
Ascot CC Pan

DRAWING No. : TPD - WC / 16 - 01

REV No : 0

SIZE : A4

SCALE : NTS

SHEET : 1 Of 1